

# Kv-værdier for Viega Easytop termostatiske cirkulationsventiler.

Indregulering af ventiler.




Model 2281.7

D = 15, 18, 22



Model 2281.3

G = ¾, 1

Gennemstrømningstemperatur [°C]

| Temperaturindstilling [°C] |      |      |      |      |      | pos. II                              | pos. II                                |
|----------------------------|------|------|------|------|------|--------------------------------------|--|
| T 52                       | T 53 | T 54 | T 55 | T 56 | T 57 | Kv [m <sup>3</sup> /h]<br>(Δp 1 bar) | Kv [m <sup>3</sup> /h]<br>(Δp 0,1 bar) |
| 52,0                       | 53,0 | 54,0 | 55,0 | 56,0 | 57,0 | 0,060                                | 0,019                                  |
| 51,5                       | 52,5 | 53,5 | 54,5 | 55,5 | 56,5 | 0,097                                | 0,031                                  |
| 51,0                       | 52,0 | 53,0 | 54,0 | 55,0 | 56,0 | 0,134                                | 0,042                                  |
| 50,5                       | 51,5 | 52,5 | 53,5 | 54,5 | 55,5 | 0,171                                | 0,054                                  |
| 50,0                       | 51,0 | 52,0 | 53,0 | 54,0 | 55,0 | 0,208                                | 0,066                                  |
| 49,5                       | 50,5 | 51,5 | 52,5 | 53,5 | 54,5 | 0,245                                | 0,077                                  |
| 49,0                       | 50,0 | 51,0 | 52,0 | 53,0 | 54,0 | 0,281                                | 0,089                                  |
| 48,5                       | 49,5 | 50,5 | 51,5 | 52,5 | 53,5 | 0,318                                | 0,101                                  |
| 48,0                       | 49,0 | 50,0 | 51,0 | 52,0 | 53,0 | 0,355                                | 0,112                                  |
| 47,5                       | 48,5 | 49,5 | 50,5 | 51,5 | 52,5 | 0,392                                | 0,124                                  |
| 47,0                       | 48,0 | 49,0 | 50,0 | 51,0 | 52,0 | 0,429                                | 0,136                                  |
| 46,5                       | 47,5 | 48,5 | 49,5 | 50,5 | 51,5 | 0,466                                | 0,147                                  |
| 46,0                       | 47,0 | 48,0 | 49,0 | 50,0 | 51,0 | 0,503                                | 0,159                                  |
| 45,5                       | 46,5 | 47,5 | 48,5 | 49,5 | 50,5 | 0,540                                | 0,171                                  |
| 45,0                       | 46,0 | 47,0 | 48,0 | 49,0 | 50,0 | 0,577                                | 0,182                                  |
| 44,5                       | 45,5 | 46,5 | 47,5 | 48,5 | 49,5 | 0,614                                | 0,194                                  |
| 44,0                       | 45,0 | 46,0 | 47,0 | 48,0 | 49,0 | 0,650                                | 0,206                                  |
| 43,5                       | 44,5 | 45,5 | 46,5 | 47,5 | 48,5 | 0,687                                | 0,217                                  |
| 43,0                       | 44,0 | 45,0 | 46,0 | 47,0 | 48,0 | 0,724                                | 0,229                                  |
| 42,5                       | 43,5 | 44,5 | 45,5 | 46,5 | 47,5 | 0,761                                | 0,241                                  |
| 42,0                       | 43,0 | 44,0 | 45,0 | 46,0 | 47,0 | 0,798                                | 0,252                                  |

Kv [m<sup>3</sup>/h] som funktion af pos. II, indstillet temperatur [T] og vandtemperatur [°C]